



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

INSPECT & TEST INJECTOR BEFORE USING IT:

1. Visually inspect injector for any damaged or missing parts.
2. Be sure the tall gridded calibration ring and thin gridded locking ring are screwed downward as far as they will go.
3. Be sure the white plastic collar above the tank is tight.
4. Be sure the round metal depth gauge is in the lowest indented notch on the probe.
5. Put a couple cups of plain water into the injector tank.
6. Pump the handle stoutly several times to be sure water squirts out 6-8 feet in all four directions. If an emitter hole in the tip is clogged, clean it carefully with a metal paperclip.
7. To test the calibration, place the injector tip into a heavy duty measuring cup and pump the handle smartly 12 times. If you get **exactly 2 ounces of liquid from 12 pumps**, the injector is working properly. If not, call the Hemlock Help Line for instructions on how to adjust the mixing ratio.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19

More on other side →



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

INSPECT & TEST INJECTOR BEFORE USING IT:

1. Visually inspect injector for any damaged or missing parts.
2. Be sure the tall gridded calibration ring and thin gridded locking ring are screwed downward as far as they will go.
3. Be sure the white plastic collar above the tank is tight.
4. Be sure the round metal depth gauge is in the lowest indented notch on the probe.
5. Put a couple cups of plain water into the injector tank.
6. Pump the handle stoutly several times to be sure water squirts out 6-8 feet in all four directions. If an emitter hole in the tip is clogged, clean it carefully with a metal paperclip.
7. To test the calibration, place the injector tip into a heavy duty measuring cup and pump the handle smartly 12 times. If you get **exactly 2 ounces of liquid from 12 pumps**, the injector is working properly. If not, call the Hemlock Help Line for instructions on how to adjust the mixing ratio.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19

More on other side →



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

INSPECT & TEST INJECTOR BEFORE USING IT:

1. Visually inspect injector for any damaged or missing parts.
2. Be sure the tall gridded calibration ring and thin gridded locking ring are screwed downward as far as they will go.
3. Be sure the white plastic collar above the tank is tight.
4. Be sure the round metal depth gauge is in the lowest indented notch on the probe.
5. Put a couple cups of plain water into the injector tank.
6. Pump the handle stoutly several times to be sure water squirts out 6-8 feet in all four directions. If an emitter hole in the tip is clogged, clean it carefully with a metal paperclip.
7. To test the calibration, place the injector tip into a heavy duty measuring cup and pump the handle smartly 12 times. If you get **exactly 2 ounces of liquid from 12 pumps**, the injector is working properly. If not, call the Hemlock Help Line for instructions on how to adjust the mixing ratio.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19

More on other side →



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

INSPECT & TEST INJECTOR BEFORE USING IT:

1. Visually inspect injector for any damaged or missing parts.
2. Be sure the tall gridded calibration ring and thin gridded locking ring are screwed downward as far as they will go.
3. Be sure the white plastic collar above the tank is tight.
4. Be sure the round metal depth gauge is in the lowest indented notch on the probe.
5. Put a couple cups of plain water into the injector tank.
6. Pump the handle stoutly several times to be sure water squirts out 6-8 feet in all four directions. If an emitter hole in the tip is clogged, clean it carefully with a metal paperclip.
7. To test the calibration, place the injector tip into a heavy duty measuring cup and pump the handle smartly 12 times. If you get **exactly 2 ounces of liquid from 12 pumps**, the injector is working properly. If not, call the Hemlock Help Line for instructions on how to adjust the mixing ratio.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19

More on other side →



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

FILL INJECTOR TANK:

- Mix treatment product per SGH application instructions.
- Position injector at 45° angle so fill cap is facing up.
- Pour mixture through a funnel & paint filter slowly into tank.
- Replace fill cap & begin using injector immediately.

USE INJECTOR:

- Use upper body strength to push probe into ground 4 – 6 inches. Do not use depth gauge for foot pressure.
- Keep using injector continuously until tank is empty.
- Then refill and continue using or clean immediately.

CLEAN INJECTOR:

- Put 2 cups of water in tank, shake vigorously in all directions, and pump it through. Repeat 2 more times.
- Store injector upside down where it won't be subject to freezing.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

FILL INJECTOR TANK:

- Mix treatment product per SGH application instructions.
- Position injector at 45° angle so fill cap is facing up.
- Pour mixture through a funnel & paint filter slowly into tank.
- Replace fill cap & begin using injector immediately.

USE INJECTOR:

- Use upper body strength to push probe into ground 4 – 6 inches. Do not use depth gauge for foot pressure.
- Keep using injector continuously until tank is empty.
- Then refill and continue using or clean immediately.

CLEAN INJECTOR:

- Put 2 cups of water in tank, shake vigorously in all directions, and pump it through. Repeat 2 more times.
- Store injector upside down where it won't be subject to freezing.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

FILL INJECTOR TANK:

- Mix treatment product per SGH application instructions.
- Position injector at 45° angle so fill cap is facing up.
- Pour mixture through a funnel & paint filter slowly into tank.
- Replace fill cap & begin using injector immediately.

USE INJECTOR:

- Use upper body strength to push probe into ground 4 – 6 inches. Do not use depth gauge for foot pressure.
- Keep using injector continuously until tank is empty.
- Then refill and continue using or clean immediately.

CLEAN INJECTOR:

- Put 2 cups of water in tank, shake vigorously in all directions, and pump it through. Repeat 2 more times.
- Store injector upside down where it won't be subject to freezing.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19



CARE & USE OF KIORITZ INJECTOR

If you have problems or questions, call 706-429-8010.

FILL INJECTOR TANK:

- Mix treatment product per SGH application instructions.
- Position injector at 45° angle so fill cap is facing up.
- Pour mixture through a funnel & paint filter slowly into tank.
- Replace fill cap & begin using injector immediately.

USE INJECTOR:

- Use upper body strength to push probe into ground 4 – 6 inches. Do not use depth gauge for foot pressure.
- Keep using injector continuously until tank is empty.
- Then refill and continue using or clean immediately.

CLEAN INJECTOR:

- Put 2 cups of water in tank, shake vigorously in all directions, and pump it through. Repeat 2 more times.
- Store injector upside down where it won't be subject to freezing.

© 2012 Save Georgia's Hemlocks. Rev. 6-12-19